



ITEM	PART	MATERIAL	DESCRIPTION	QTY
1	Array lid	Glass	3.5x5x1	1
2	Array base	Glass	16V-127P-3.5x12x5x1.5t	1
3	Cladding fiber	Glass	/	16
4	Bare fiber	Glass+Acrylate	Corning SMF-28 Ultra fiber	16
5	Fiber jacket	Hytrell	0.9mm white loose tube	16
6	Fiber Connector	Nickel plated brass	FC/APC	16
7	Wear cable marker	Polyethylene	Number : 1-16	16

REV.	DESCRIPTION	DATE	REVISED
A		2024/1/5	D2

DIMENSIONS ARE IN MM		NAME	DATE	
X ± 0.15 .X ± 0.10 .XX ± 0.05 ANGULAR ± 0.5°		DRAWN	D2	
ALL MACHINED SURFACE TO BE $3.2 \sqrt{\text{V}}$		Q.A.	Q1	2024/1/5
BREAK SHARP CORNERS MAX		PROPRIETARY AND CONFIDENTIAL THE INFORMATION CONTAINED IN THIS DRAWING IS THE SOLE PROPERTY OF PHIX PHOTONICS ASSEMBLY. ANY REPRODUCTION IN PART OR AS A WHOLE WITHOUT THE WRITTEN PERMISSION OF PHIX PHOTONICS ASSEMBLY IS PROHIBITED.		TITLE: LX-16ch 127P SMFA-FC_APC
SIZE	PART NO. or DWG. NO.	REV		
A4	30110822 153244	A		
SCALE:1:1		SHEET 1 OF 1		